

STANDARD PHRASEOLOGY

SECTION A

1. This section of standard phraseology contains the approved standard phrases to be used when invoking Category II Standard Items. The Standard Item number and title are provided at the top of each phrase or group of phrases associated with the Standard Item list.

SI

A3 PHRASE DELETED

A5 PHRASE DELETED

A6 PHRASE DELETED

009-09 PROCESS CONTROL PROCEDURE (PCP); PROVIDE AND ACCOMPLISH

Accomplish the requirements of 009-09 of 2.1 for ____.

A9

009-11 INSULATION AND LAGGING REQUIREMENTS; ACCOMPLISH

NOTE: NOT TO BE USED FOR INTERFERENCE REPLACEMENTS COVERED BY
009-23. USE A-11 TO INSTALL NEW PIPING, MACHINERY, AND HULL
INSULATION AND LAGGING.

CONSIDERATION SHALL BE GIVEN TO HIGH TRAFFIC AREAS AS DEFINED
IN 4.2 OF MIL-STD-769.

Accomplish the requirements of 009-11 of 2.1 for _____.

A11

009-12 WELDING, FABRICATION, AND INSPECTION REQUIREMENTS; ACCOMPLISH

NOTE: A12b SHALL BE A SUBPARAGRAPH OF A12a IF MORE THAN A VISUAL INSPECTION IS REQUIRED.

Accomplish the requirements of 009-12 of 2.1, including Table ____, Column(s) ____, Lines One through ____.

A12a

NOTE: A12b SHALL BE USED ONLY AS A SUBPARAGRAPH TO A12a. THIS PHRASE CANNOT BE USED TO SPECIFY NDT REQUIREMENTS NOT ASSOCIATED WITH WELDING OR BRAZING. SEE B25 AND B26.

Accomplish nondestructive testing in accordance with Line ____.

A12b

Accomplish the requirements of 009-12 of 2.1, including Table ____, Column(s) ____, Lines One through ____, for ____.

A12c

009-13 METERS; REPAIR AND CALIBRATE

Accomplish the requirements of 009-13 of 2.1 for each ____ listed in ____, **using 2.____ for guidance.**

A13a MONEY PHRASE MOVED TO B50

Calibrate and adjust each new meter in accordance with 009-13 of 2.1.

A13b

009-14 GAGES AND THERMOMETERS; REPAIR AND CALIBRATE

Accomplish the requirements of 009-14 of 2.1 for each ____.

A14a MONEY PHRASE MOVED TO B50

Calibrate and adjust each new gage and/or thermometer in accordance with 009-14 of 2.1.

A14b

009-15 ROTATING MACHINERY; BALANCE

Accomplish the requirements of 009-15 of 2.1 for each rotating assembly.

A15

009-16 ELECTRONIC EQUIPMENT; REPAIR

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL IN REFERENCES.

Accomplish the requirements of 009-16 of 2.1 for the ____ listed in ____, using 2.__ for guidance.

A16 MONEY PHRASE MOVED TO B50

009-17 ROTATING ELECTRICAL EQUIPMENT; REPAIR

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL IN REFERENCES.

Accomplish the requirements of 009-17 of 2.1 for the equipment listed in 1.3.__, using 2.__ for guidance.

A17

009-22 SHIPBOARD ELECTRIC CABLE; TEST

Accomplish the requirements of 009-22 of 2.1 for the cable(s) terminating in the equipment listed in ____.

A22

A23a PHRASE DELETED

A23b PHRASE DELETED

009-25 STRUCTURAL BOUNDARY TEST; ACCOMPLISH

Accomplish the requirements of 009-25 of 2.1 for preliminary air test of ____.
Test pressure shall be ____ PSIG.

A25a

NOTE: USE A25b FOR TANKS, VOIDS, AND COFFERDAMS. THE ALLOWABLE DROP OUNCES PER SQUARE INCH FOR WIRING TRUNK AND OTHER SPACES ARE 5 AND 2 RESPECTIVELY.

Accomplish the requirements of 009-25 of 2.1 for air test of _____. Test pressure shall be _____ PSIG. Maintain test pressure for 15 minutes for temperature stabilization prior to start of test. Hold test pressure for 10 minutes. Allowable drop in pressure: None.

A25b

NOTE: SALT WATER SHALL BE SPECIFIED FOR USE ON WOOD.

Accomplish the requirements of 009-25 of 2.1 for the _____ hose test of _____. Allowable leakage: None.

A25c

Accomplish the requirements of 009-25 of 2.1 for the vacuum box test of _____. Allowable leakage: None.

A25d

009-26 TELETYPE EQUIPMENT; REPAIR

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL IN REFERENCES.

Accomplish the requirements of 009-26 of 2.1 for equipment listed in _____, using 2.____ for guidance.

A26 MONEY PHRASE MOVED TO B50

009-27 MATERIAL IDENTIFICATION AND CONTROL (MIC) FOR PIPING SYSTEMS;
ACCOMPLISH

Accomplish the requirements of 009-27 of 2.1.

A27

009-28 METAL SPRAYED COATING SYSTEM FOR CORROSION PROTECTION; ACCOMPLISH

NOTE: USE WHEN WIRE SPRAY ALUMINUM COATING VALVES, PIPING, DECK HARDWARE, WATERTIGHT DOORS, LIGHTING FIXTURES, AND BRACKETS.

Accomplish the requirements of 009-28 of 2.1 for _____.

A28

009-30 BOILER SAMPLE TUBES; INSPECT

Accomplish the requirements of 009-30 of 2.1.

A30

009-31 BOILER WATERJET CLEANING; ACCOMPLISH

Accomplish the requirements of 009-31 of 2.1.

A31

009-32 CLEANING AND PAINTING REQUIREMENTS; ACCOMPLISH

NOTE: USE A32a WHEN MAIN ITEM IS PRESERVATION AND THE TABLES IN 009-32 PROVIDE A CHOICE. USE A32b FOR OTHER PRIMARY PRESERVATION WORK AND TOUCH-UP. SPECIFY DEGREE OF PRESERVATION, i.e., FOUNDATION, NEW AND DISTURBED SURFACES, NORMALLY PRESERVED SURFACES.

Accomplish the requirements of 009-32 of 2.1, including Table ___, Line(s) ___, for _____.

A32a

Accomplish the requirements of 009-32 of 2.1 for _____.

A32b

Accomplish the requirements of 009-32 of 2.1, including Table ___, Line(s) ___, Column(s) ___ for _____.

A32c

009-33 ROTATING ELECTRICAL EQUIPMENT; REWIND

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL IN REFERENCES.

Accomplish the requirements of 009-33 of 2.1 for equipment listed in 1.3.__, using 2.__ for guidance.

A33

009-36 CONTROLLER; REPAIR

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL IN REFERENCES.

Accomplish the requirements of 009-36 of 2.1 for each controller listed in _____, using 2.____ for guidance.

A36 MONEY PHRASE MOVED TO B50

009-37 GENERAL PROCEDURES FOR WOODWORK; ACCOMPLISH

NOTE: INVOKE IN WORK ITEMS REQUIRING WOOD REPAIRS/NEW INSTALLATIONS.

Accomplish the requirements of 009-37 of 2.1 for _____.

A37a

NOTE: A37b SHALL BE USED ONLY AS A SUBPARAGRAPH TO A37a. INVOKE A37b WHEN ACCOMPLISHING REPAIRS/NEW INSTALLATIONS OF DECK PLANK CAULKING SEAMS.

Caulking compound for deck plank caulking seams shall be _____.

A37b

009-38 BOILER DRY LAY-UP; ACCOMPLISH

Accomplish the requirements of 009-38 of 2.1 for _____.

A38

A39 PHRASE DELETED

A40 PHRASE DELETED

009-41 TECHNICAL MANUAL CONTRACT REQUIREMENT (TMCR) FOR A TOPICALLY STRUCTURED MANUAL; PROVIDE

NOTE: USE FOR NEW MILITARY TECHNICAL MANUALS FOR NON-COMPLEX EQUIPMENT BEING PROCURED TO MILITARY SPECIFICATIONS.

Accomplish the requirements of 009-41 of 2.1.

A41

009-42 TECHNICAL MANUAL CONTRACT REQUIREMENT (TMCR) FOR UPDATING TECHNICAL MANUALS; PROVIDE

NOTE: USE FOR UPDATING EXISTING NAVSEA TECHNICAL MANUALS (INCLUDING SHIP'S SELECTED RECORD DATA) TO REFLECT CHANGES IN HARDWARE CONFIGURATION.

Accomplish the requirements of 009-42 of 2.1.

A42

009-43 LIGHT-OFF ASSESSMENT (LOA) SUPPORT FOR STEAM PROPULSION SYSTEM; PROVIDE

Accomplish the requirements of 009-43 of 2.1.

A43

009-44 LIGHT-OFF ASSESSMENT (LOA) SUPPORT FOR GAS TURBINE PROPULSION SYSTEM; PROVIDE

Accomplish the requirements of 009-44 of 2.1.

A44

NOTE: FOR STANDARD ITEMS 009-45, 009-46, 009-47, 009-48, 009-50, 009-51, 009-52, 009-53, 009-55, AND 009-96, VALVE REMOVAL AND REINSTALLATION SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

009-45 TAPERED PLUG VALVE; REPAIR

NOTE: **A45b SHALL BE A SUBPARAGRAPH TO A45a.**

FOR SHOP REPAIR AND TEST.

TEST PRESSURE FOR SEAT TIGHTNESS SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

Accomplish the requirements of 009-45 of 2.1 for each plug valve listed in ____, using 2.____ for guidance.

A45a

The seat tightness test pressure is ____ PSIG.

A45b

009-46 BUTTERFLY VALVE, SYNTHETIC AND METAL SEATED; REPAIR

NOTE: **A46b SHALL BE A SUBPARAGRAPH TO A46a.**

FOR SHOP REPAIR AND TEST.

TEST PRESSURE FOR SEAT TIGHTNESS SHALL BE SPECIFIED IN THE
INVOKING WORK ITEM.

Accomplish the requirements of 009-46 of 2.1 for each butterfly valve listed in ____, using 2.____ for guidance.

A46a

The seat tightness test pressure is ____ PSIG.

A46b

009-47 GATE VALVE; REPAIR

NOTE: **A47b SHALL BE A SUBPARAGRAPH TO A47a.**

FOR SHOP REPAIR AND TEST.

TEST PRESSURE FOR SEAT TIGHTNESS SHALL BE SPECIFIED IN THE
INVOKING WORK ITEM. SHALL NOT BE USED FOR HIGH PRESSURE STEAM
VALVES.

Accomplish the requirements of 009-47 of 2.1 for each gate valve listed in ____, using 2.____ for guidance.

A47a

The seat tightness test pressure is ____ PSIG.

A47b

009-48 PRESSURE SEAL BONNET VALVE; REPAIR (SHOP)

NOTE: **A48b SHALL BE A SUBPARAGRAPH TO A48a.**

FOR SHOP REPAIR AND TEST.

TEST PRESSURE FOR SEAT TIGHTNESS SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

Accomplish the requirements of 009-48 of 2.1 for each pressure seal bonnet valve listed in ____, using 2.__ for guidance.

A48a

The seat tightness test pressure is ____ PSIG.

A48b

009-49 PRESSURE SEAL BONNET VALVE; REPAIR (IN-LINE)

NOTE: FOR IN-LINE REPAIR.

OPERATIONAL TEST OF THE VALVE SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

Accomplish the requirements of 009-49 of 2.1 for each in-line pressure seal bonnet valve listed in ____, using 2.__ for guidance.

A49

009-50 HORIZONTAL SWING CHECK VALVE; REPAIR

NOTE: FOR SHOP REPAIR AND TEST.

SHALL NOT BE USED FOR SCUPPER VALVES.

Accomplish the requirements of 009-50 of 2.1 for each check valve listed in ____, using 2.__ for guidance.

A50

009-51 GLOBE, GLOBE ANGLE, AND GLOBE STOP CHECK VALVE; REPAIR

NOTE: **A51b SHALL BE A SUBPARAGRAPH TO A51a.**

FOR SHOP REPAIR AND TEST.

TEST PRESSURE FOR SEAT TIGHTNESS SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

SHALL NOT BE USED FOR HIGH PRESSURE STEAM VALVES.

Accomplish the requirements of 009-51 of 2.1 for each globe valve listed in ____, using 2.__ for guidance.

A51a

The seat tightness test pressure is ____ PSIG.

A51b

009-52 RELIEF VALVE; REPAIR

NOTE: **A52b-A52d SHALL BE SUBPARAGRAPHS TO A52a.**

FOR SHOP REPAIR AND TEST.

TEST MEDIUM AND TEST PRESSURE FOR SEAT TIGHTNESS AND VALVE LIFTING SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

SHALL NOT BE USED FOR BOILER SAFETY VALVES.

Accomplish the requirements of 009-52 of 2.1 for each relief valve listed in ____, using 2.__ for guidance.

A52a

The test medium is ____.

A52b

The seat tightness test pressure is ____ PSIG.

A52c

The lifting pressure is ____ PSIG.

A52d

009-53 BOLTED BONNET STEAM VALVE; REPAIR (SHOP)

NOTE: **A53b SHALL BE A SUBPARAGRAPH TO A53a.**

FOR SHOP REPAIR AND TEST.

TEST PRESSURE FOR SEAT TIGHTNESS SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

Accomplish the requirements of 009-53 of 2.1 for each bolted bonnet steam valve listed in ____, using 2.__ for guidance.

A53a

The seat tightness test pressure is ____ PSIG.

A53b

009-54 BOLTED BONNET STEAM VALVE; REPAIR (IN-LINE)

NOTE: FOR IN-LINE REPAIR.

OPERATIONAL TEST OF THE VALVE, INCLUDING BYPASS VALVE, SHALL BE SPECIFIED IN WORK ITEM.

Accomplish the requirements of 009-54 of 2.1 for each in-line bolted bonnet steam valve listed in ____, using 2.__ for guidance.

A54

009-55 REGULATING/REDUCING VALVE; REPAIR

NOTE: **A55b-A55c SHALL BE SUBPARAGRAPHS TO A55a.**

FOR SHOP REPAIR AND TEST.

TEST MEDIUM AND TEST PRESSURE FOR VALVE INLET AND REGULATED PRESSURE/TEMPERATURE SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

NOTE: **A55a-A55c SHALL BE USED FOR PRESSURE REGULATORS/REDUCERS ONLY.**

Accomplish the requirements of 009-55 of 2.1 for each regulating/reducing valve listed in ____, using 2.__ for guidance.

A55a

The test medium is ____.

A55b

The regulated pressure is ____ PSIG.

A55c

NOTE: **A55e-A55f SHALL BE SUBPARAGRAPHS TO A55d.**

A55d-A55f SHALL BE USED FOR TEMPERATURE REGULATORS ONLY.

Accomplish the requirements of 009-55 of 2.1 for each regulating/reducing valve listed in ____, using 2.____ for guidance.

A55d

The test medium is ____.

A55e

The regulated temperature is ____ degrees Fahrenheit.

A55f

009-56 BOILER WET LAY-UP; ACCOMPLISH

Accomplish the requirements of 009-56 of 2.1 for ____.

A56

009-57 REDUCTION GEAR SECURITY REQUIREMENTS; ACCOMPLISH

NOTE: **A57 TO BE INVOKED AS 3.1 IN WORK ITEMS WHERE REDUCTION GEAR SECURITY IS AFFECTED.**

Accomplish the requirements of 009-57 of 2.1.

A57

009-58 PUMP AND DRIVER SHAFT ALIGNMENT; ACCOMPLISH

NOTE: A58 TO BE INVOKED ANY TIME THE ROTOR OF A PUMP OR DRIVER
(MOTOR/TURBINE) IS DISTURBED FOR REPAIR OR REPLACEMENT.

Accomplish the requirements of 009-58 of 2.1 for _____.

A58

009-60 PHRASE DELETED

009-62 BOILER HANDHOLE AND MANHOLE SEATS AND PLATES; INSPECT

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL IN REFERENCES.

Accomplish the requirements of 009-62 of 2.1 for ____.

A62

009-63 LUBRICATING OILS AND HYDRAULIC FLUIDS; ANALYZE

NOTE: **A63b SHALL** BE A SUBPARAGRAPH TO A63a.

SPECIFY QUANTITY AND TYPE OF SAMPLE.

Accomplish the requirements of 009-63 of 2.1.

A63a

Test and analyze _____ samples.

A63b

NOTE: **A63c** WILL BE A SUBPARAGRAPH TO A63a-**A63b**, AS APPLICABLE.

SPECIFY THE LOCATION FROM WHICH SAMPLES OF LUBRICATING OR
HYDRAULIC FLUIDS ARE TO BE TAKEN.

Take a sample from _____ in accordance with ASTM D4057.

A63c

009-66 LIGHT-OFF ASSESSMENT (LOA) SUPPORT FOR DIESEL PROPULSION SYSTEM;
PROVIDE

Accomplish the requirements of 009-66 of 2.1.

A66

009-67 PHRASE DELETED

009-68 BOLTED BONNET VALVE; REPAIR

NOTE: FOR IN-LINE REPAIR.

OPERATIONAL TEST OF THE VALVE SHALL BE SPECIFIED IN THE
INVOKING WORK ITEM.

Accomplish the requirements of 009-68 of 2.1 for each in-line bolted bonnet valve listed in ____, using 2.__ for guidance.

A68

009-71 TESTING REQUIREMENTS FOR PIPING SYSTEMS; ACCOMPLISH

NOTE: INVOKE A71a FOR NON-PRESSURIZED SYSTEMS ONLY.

Accomplish the requirements of 009-71 of 2.1 for new and disturbed piping.

A71a

NOTE: **A71b-A71g ARE** FOR USE WITH REDUCED OR HIGH ENERGY SYSTEMS.
CONTRACTOR MAY OPTION TO ACCOMPLISH A HYDROSTATIC TEST IN LIEU
OF OPERATING PRESSURE TEST. TEST PRESSURE AND TEST MEDIUM
SHALL BE LISTED.

Accomplish the requirements of 009-71 of 2.1 for new and disturbed piping.

A71b

Test pressure shall be ____ PSIG, using clean, fresh water, when the hydrostatic test option is selected.

A71c

Accomplish the requirements of 009-71 of 2.1 for new and disturbed piping.

A71d

Test pressure shall be ____ PSIG, using feedwater conforming to Paragraphs 220-22.16 through 220-22.22 of 2.____, when the hydrostatic test option is selected.

A71e

Accomplish the requirements of 009-71 of 2.1 for new and disturbed piping.

A71f

Test pressure shall be ____ PSIG, using ____, when the hydrostatic test option is selected.

A71g

NOTE: A71H-A71k ARE FOR USE WITH HIGH ENERGY SYSTEMS. PLANNER MUST USE THIS PHRASEOLOGY WHEN A HYDROSTATIC TEST IS REQUIRED (NSTM 505) AS IN THE CASE OF THE EXCLUSIONARY PIPING SYSTEMS AND WHEN NEW PIPING, COMPONENTS, AND VALVES ARE BEING INSTALLED. TEST PRESSURE AND TEST MEDIUM SHALL BE LISTED (A71e-A71g).

Accomplish the requirements of 009-71 of 2.1 for hydrostatic test, using clean, fresh water at ____ PSIG.

A71h

Accomplish the requirements of 009-71 of 2.1 for hydrostatic test, using feedwater at ____ PSIG.

A71i

Feedwater shall conform to Paragraphs 220-22.17 through 220-22.22 of 2.____.

A71j

Accomplish the requirements of 009-71 of 2.1 for hydrostatic test, using ____ at ____ PSIG.

A71k

NOTE: USE A71l FOR AIR TEST OF CRITICAL SYSTEMS.

Accomplish the requirements of 009-71 of 2.1 for new and disturbed _____ piping, using clean, dry air at ____ PSIG.

A71l

009-75 CIRCUIT BREAKER; REPAIR

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL IN REFERENCES.

Accomplish the requirements of 009-75 of 2.1 for _____, using 2.____ for guidance.

A75 MONEY PHRASE MOVED TO B50

009-76 WAVEGUIDE AND TRANSMISSION LINE TEMPORARY LAY-UP, PRESSURIZATION, AND PURGING; ACCOMPLISH

Accomplish the requirements of 009-76 of 2.1 for ____.

A76

009-77 ***PHRASE DELETED***

009-78 PASSIVE COUNTERMEASURES SYSTEM MATERIAL REQUIREMENTS; ACCOMPLISH

Accomplish the requirements of 009-78 of 2.1.

A78

009-82 PHRASE DELETED

009-83 PHRASE DELETED

009-85 GOVERNMENT SPONSORED PLANNING YARD/CONFIGURATION DATA MANAGER (CDM)
ON-SITE REPRESENTATIVE FACILITY; PROVIDE

Accomplish the requirements of 009-85 of 2.1.

A85

009-86 PHRASE DELETED

009-87 PHRASE DELETED

009-89 PHRASE DELETED

009-90 TECHNICAL REPRESENTATIVE; PROVIDE

NOTE: USE A90b AS A SUBPARAGRAPH TO A90a WHEN TECHNICAL SUPPORT, SPECIAL TOOLS, AND/OR EQUIPMENT ARE REQUIRED.

Accomplish the requirements of 009-90 of 2.1.

A90a

Provide the services of a _____ technical representative to _____.

A90b

Accomplish the requirements of 009-90 of 2.1 for ____.

A90c

009-91 PROPELLER IN-PLACE INSPECTION; ACCOMPLISH

Accomplish the requirements of 009-91 of 2.1 for equipment listed in ____.

A91

009-92 RESILIENT MOUNT; INSTALL

NOTE: INSERT EQUIPMENT TECHNICAL MANUAL.

Accomplish the requirements of 009-92 of 2.1 for equipment listed in ____, using 2.__ for guidance.

A92

009-96 BALL VALVE; REPAIR

NOTE: A96b SHALL BE A SUBPARAGRAPH TO A96a.

FOR SHOP REPAIR AND TEST. TEST PRESSURE FOR SEAT TIGHTNESS SHALL BE SPECIFIED IN THE INVOKING WORK ITEM.

Accomplish the requirements of 009-96 of 2.1 for each ball valve listed in ____, using 2.__ for guidance.

A96a

The seat tightness test pressure is ____ PSIG.

A96b

009-98 MONEL FASTENERS; INSPECT

Accomplish the requirements of 009-98 of 2.1.

Remove existing and install new up to ____ percent of fasteners.

A98

009-104 VIBRATION TESTING AND ANALYSIS; ACCOMPLISH

Accomplish the requirements of 009-104 of 2.1.

A104

009-105 THERMAL SPRAYED COATINGS FOR MACHINERY COMPONENT REPAIR; ACCOMPLISH

NOTE: USE WHEN THERMAL SPRAY COATING (EXCEPT ALUMINUM) MACHINERY COMPONENTS. SPECIFY THE TYPE OF COATING MATERIAL AND EITHER WIRE SPRAY OR POWDER SPRAY PROCESS.

Accomplish the requirements of 009-105 of 2.1 for the ____ listed in 1._.
The coating material shall be ____, using the ____ spray process.

A105